

Electric Pallet Stacker

Model:

T-CTD10R-E

T-CTD12R-E

T-CTD15R-E

Straddle legs
&
Adjustable forks

The super light Electric Walkie.
Stacker with small turning radius
which is widely used in small
warehouse and super market.

Suit for low level stacking and
short distance transportation.


Super Compact



CE Conforms to
EN ISO3691-1
EN1175-1
EN16307-1



Tiller Head



Floor type drive wheel

Model		T-CTD10R-E	T-CTD12R-E	T-CTD15R-E
Load capacity	Q (kg)	1000	1200	1500
Load centre distance	C (mm)	600	600	600
Load distance, centre of drive axle to fork	X (mm)	770	770	770
Height (lowered)	h13 (mm)	80	80	80
Tyre size (front)		Ø195 x 70	Ø195 x 70	Ø195 x 70
Tyre size (rear)		Ø98 x 82	Ø98 x 82	Ø98 x 82
Additional wheels (dimensions)		Ø150 x 60	Ø150 x 60	Ø150 x 60
Wheels, number front rear (x = driven wheels)		1x + 1/4	1x + 1/4	1x + 1/4
Height, mast lowered	h1 (mm)	2145 / 1895 / 2145	2145 / 1895 / 2145	2140 / 1890 / 2140
Max. lift height	h3 (mm)	1600 / 2500 / 3000	1600 / 2500 / 3000	1600 / 2500 / 3000
Height, mast extended	h4 (mm)	2145 / 3100 / 3600	2145 / 3100 / 3600	2145 / 3100 / 3600
Height of tiller in drive position min./max.	h14 (mm)	670 / 1300	670 / 1300	670 / 1300
Overall length	L1 (mm)	1500	1500	1500
Length to face of forks	L2 (mm)	660	660	660
Overall width	b1 (mm)	800	800	800
Fork dimensions	mm	35 x 100 x 1070 (1150)	35 x 100 x 1070 (1150)	35 x 100 x 1070 (1150)
Width overall forks	b5 (mm)	200 ~ 800	200 ~ 800	200 ~ 800
Ground clearance, centre of wheelbase	m2 (mm)	35	35	35
Aisle width for pallets 1000x1200 crossways	Ast (mm)	2280	2280	2280
Aisle width for pallets 800x1200 lengthways	Ast (mm)	2280	2280	2280
Turning radius	Wa (mm)	1490	1490	1490
Travel speed (laden / unladen)	km/h	4.5 / 5	4.5 / 5	4.5 / 5
Lift speed (laden / unladen)	mm/s	90 / 140	90 / 140	80 / 110
Lowering speed (laden / unladen)	mm/s	120 / 100	120 / 100	120 / 100
Battery voltage, nominal capacity K20	V/Ah	24 / 105	24 / 105	24 / 125
Battery weight	kg	52	52	70
Battery dimensions (L x W x H)	mm	260 x 168 x 217	260 x 168 x 217	330 x 171 x 217
Service weight (with battery)	kg	490 / 555 / 575	490 / 555 / 575	580 / 645 / 665

